



THE CASK

WOOD SPECIFICATIONS

Type	Quercus Sessilis, Quercus Robur
Origin	Selection et assembly of numerous french sources
Ageing	Open air ageing
Quality Control	Test of non contaminating agent : TCA/Radioactivity

STAINLESS ACCESSORIES 316 L INCLUDED

Aseptic bung Bellot Type VOG 210	Racking port - Valve with ball Ø 40 Mâcon
Base of the bung	Bars on heads
Taster Garnier Geoffroy with purge	Oak tain for raising height (+45cm)
Porte ovale verticale autoclave 307x442 Boyer	Alimentary varnished
Drain port - Valve Mâcon with ball Ø 40	Black painted hoops



BYCert. 6091858

STANDARD DIMENSIONS*

Thickness	Volume	Back from head	Hoops	Staves lenght	Head diameter	Bilge diameter
54 mm	10 hl	70 mm	8 galvanized	126 cm	114 cm	126 cm
54 mm	15 hl	70 mm	8 galvanized	142 cm	129 cm	142 cm
54 mm	20 hl	70 mm	8 galvanized	154 cm	141 cm	154 cm
54 mm	25 hl	70 mm	8 galvanized	165 cm	152 cm	165 cm
54 mm	30 hl	70 mm	8 galvanized	175 cm	161 cm	175 cm
54 mm	40 hl	70 mm	8 galvanized	190 cm	171 cm	190 cm
65 mm	50 hl	70 mm	8 galvanized	205 cm	191 cm	205 cm

*Possibility of manufacturing of custom-made casks

GENERAL CONCEPT OF CASK

Cask length = bilge diameter



Completion of staves heads:
Flat chime of 3mm

Completion of oak tain :
Flat chime of 3mm

Oak tain 10 cm back from cask head edge

Transversal oak tain 15 x15 cm = Head diameter

Longitudinal oak tain 15 x15 cm = Cask length - 10 cm